

UMBRELLA AND UMBRELLA STANDS

Number: BURL-088
 Creation Date: 12/19/2017
 Revision Date: 4/11/2019
 Created by: Legal Dept.

TEST DESCRIPTION	REGULATION/TEST METHOD	REQUIREMENTS
MANDATORY		
Label Verification	F.P. & L. Act (16 CFR 500) OR NIST Uniform Laws and Regulations Handbook 130 FTC regulation	Manufacturer, packer, or distributor's name & address (city, state & zip)
		Product Identification
		Net quantity of contents shall be expressed in terms of weight or mass, measure, numerical count, or combination so as to give accurate information to facilitate consumer comparison (U.S. and metric units).
		Fiber Content
Country of Origin Marking	19 CFR 134.11	Shall indicate country of origin legibly and permanently. Must be visible at point of purchase.
Fiber analysis (textile)	AATCC 20/20A	Single Fiber: No tolerance Blended Fiber: +/- 3%
California Prop 65	Warning label or applicable testing	In lieu of warning label, product should meet all applicable Prop 65 requirements.
Formaldehyde Emission (Composite Wood Component only)	Federal Toxic Substances Control Act, 15 U.S.C., Sec. 2697 (TSCA Title VI). and California Health & Safety Code (title 17, sections 93120 – 93120.12).	Finished product must be labeled "TSCA Title VI compliant" or "TSCA TITLE VI and NAF/ULEF Compliant" with manufacturer's name and date the finished good Formaldehyde emission requirements: HWPW-VC: ≤0.05 ppm HWPW-CC: ≤ 0.05 ppm PB: ≤ 0.09 ppm MDF: ≤ 0.11 ppm Thin-MDF: ≤ 0.13 ppm
Total heavy metals in packaging	Toxics in Packaging Clearinghouse (TPCH)	Packaging shall not contain the sum of mercury, cadmium, lead and chromium (VI) in concentration above 0.01% by weight.
Plastic Bag Warnings	Various state laws	Plastic bags with a thickness of less than 1 mil (0.001 inch) having an opened end larger than 5 inches in diameter shall contain the following warning statement or equivalent: WARNING: To avoid danger of suffocation, keep this plastic bag away from babies and children. Do not use this bag in cribs, beds, carriages or playpens. This bag is not a toy.
OPTIONAL (PERFORMANCE & QUALITY) MANDATORY		
Sharp Points / Edges	16 CFR 1500.48 / 1500.49	Shall have no sharp points or edges as received, other than those required for function.
Resistance to Corrosion (For metal component)	ASTM B117	Metal component shall withstand 24 hours in 5% salt spray (fog) with no major corrosion
Colorfastness to Light (For fabric of outdoor use article)	AATCC 16.3 (80 AFU)	For fabric of outdoor use article: Grade 4 min.
Colorfastness to Crocking (For fabric)	AATCC 8 / 116	Dry: Grade 4 min. Wet: Grade 3 min.
Water Repellency - Spray Test (For fabric)	AATCC 22	Original: Rating 90 min. After wash (if request): Rating 70 min.